

# PRODUCT SPECIFICATION

## T10



**T10** is a member of the industry's first robotically controlled line source family. Stunning SPL and clarity can be precisely controlled in both the vertical and horizontal planes, offering system operators maximum flexibility in making coverage adjustments after the array is flown. Onboard inclinometers and network-based Auto-Array within PK .dynamics software enable each module to recognize its position and angle within the system, improving accuracy, efficiency of deployment, and safety.

Dual bandpass-loaded 10" transducers manage low-frequency response. The mid-frequency band is supported by two 6.5" midrange transducers affixed to the patented Coherent Midrange Integrator (CMI). A dual-diaphragm high-frequency transducer, coupled directly to an integrated planar waveguide, significantly reduces distortion across the high-frequency band. A 3,000 W Class D amplifier maximizes headroom while maintaining crystal clear audio and exceptional output.

The CMI waveguide seamlessly combines mid and high frequencies, working in tandem with precisely spaced low-frequency apertures for smooth and controlled directivity. It allows for variable adjustability from 60°-120° both symmetrically and asymmetrically so that system designers and technicians can remotely shape the radial directivity of the array relative to the coverage requirements of any event or venue.

Flown straight, the array's directivity is then configured remotely using industrial linear actuators with a duty cycle of up to 109 years. Horizontal angles can be set to over 30 variable positions, allowing for mechanical optimization. Vertical angles are variable with 0.1° accuracy. Finally, a combination of FIR and IIR filters is applied to ensure smooth frequency response throughout the listening area.

### Output Capability

Frequency Response.....40 Hz-20 kHz  
Peak SPL.....146 dB

### Acoustic Properties

Horizontal Directivity.....60°-120° Robotic Directivity  
Horizontal Resolution.....5° Symmetric & Asymmetric  
Vertical Adjustment..... 0°-12° Robotic Directivity  
Vertical Resolution.....0.1° Increments

### Robotic Actuators

Horizontal Thrust.....750 N  
Vertical Thrust.....2,500 N  
IP Rating.....IP69K (static), IP66 (dynamic)  
Duty Cycle.....80,000 Actuations (109 years)

### Transducers

Low-Frequency.....2 x 10" Bandpass Loaded  
Mid-Frequency.....2 x 6.5" CMI Loaded  
High-Frequency.....1 x 4" Dual Diaphragm Planar Wave

### Amplification

Amplifier..... 3 Channel Class D  
Amplifier Power..... 3,000 W  
Operating Voltage..... Auto-Switching 100-240 V, 50/60 Hz  
Power Consumption.....700 W  
Network..... Proprietary

### Input/Output Connections

Input Selection.....Analog/AES  
Audio/Network..... Multipin Amphenol – IP65  
Power..... powerCON TRUE1 – IP65

### Physical Properties

Weight.....47.6 kg/105 lb  
(W x H x D)..... 980 x 250 x 561 mm  
38.58 x 9.84 x 22.09 in  
Max Line Length.....24 Modules  
Environmental.....IP42 (front), IP43 (rear)  
Multipin Connector..... IP65  
Module Construction...Void-Free, High-Grade Baltic Birch  
Rigging Construction...6061-T6 Aluminum  
External Coating.....EXL Polyurea  
Grill..... Powder Coated Aluminum

